








## Past Tested Peripherals

Mersive's past testing determined the following devices to work for video conferencing with Solstice on at least one version of Solstice with the listed device firmware. These historical testing data and performance notes are provided as a reference only. Mersive does not provide support for use of these devices with Solstice.

See the [Solstice Supported Peripherals](#) list for peripheral devices currently supported for video conferencing with Solstice.

Device Name	Part #	Latest Tested Firmware	Latest Tested Solstice Version	Notes	
AMX Acendo Vibe (ACV-5100)	FG4151-00BL-UA/EK (Black) FG4151-00GR-UA/EK (Grey)			Use USB audio device prioritization to select the built-in mic for video conference audio.	
Avaya HC020	700514534				
AVer Cam 540	COMSCA540	0.0.6004.14	5.5		
AVer Cam 520 Pro	COM520PRS	0.0.1004.18	5.3.4		
AVer Cam 520	COMSCA520	0.0.1004.42	5.3.4		
AVer Cam 340+	COMMIC34+	0.0.1000.36	5.3.4	Not supported for Solstice + Microsoft Teams on Windows. Use camera in Bulk mode. Pair with USB speakerphone to avoid a potential remote echo.	
AVer VB342+ Soundbar	COMVB342+				
Avonic CM22	AV-CM22-VCU			Pair with USB speakerphone to avoid a potential remote echo.	
Avonic CM44	AV-CM44-VCUC-B				
Cisco Webex Room Kit Mini	CS-KIT-MINI	5.5			
Clear One Unite50	910-2100-006			Pair with USB speakerphone to avoid a potential remote echo.	
Crestron SB-1 Soundbar	UC-SB1	1.4.14-105704	5.5.2		
Crestron UC-SB-1-CAM	UC-SB1-CAM	1.002.001.011	5.5	Connect camera to dedicated power supply.	
Dante AVIO USB Adapter	ADP-USB-AU-2X2	n/a	5.5.2		

Device Name	Part #	Latest Tested Firmware	Latest Tested Solstice Version	Notes	
HuddleCamHD 10X	HC10X-GY-G3 (Black) HC10X-WH-G3 (White)	4.3.6	5.4		
HuddleCamHD 3XA	HC3XA-BK (Black) HC3XA-WH (White)	4.2.5	5.4	Pair with USB speakerphone to avoid a potential remote echo.	
HuddleCamHD Pro EPTZ	HC-EPTZ-USB	8.2.83	5.4	Camera may not currently be selectable in the video conferencing app when occupancy counting for the Solstice Pod is enabled. Pair with USB speakerphone to avoid a potential remote echo.	
Huddly IQ	7090043790573	1.4.22-109426	5.5.2	Pair with USB speakerphone to avoid a potential remote echo. Plugging the Pod into the Mersive provided power supply recommended, in place of or in addition to PoE+.	
Huddly GO	7090043790009	1.3.11	5.3.4		
Jabra PanaCast	8100-119	0.3.9.15	5.5.2	Audio for microphone is sped up when video is on. Requires USB power injector or powered hub. Pair with USB speakerphone to avoid a potential remote echo.	
Jabra PanaCast 50	8200-232 (Black), 8201-232 (Grey)	1.13.4	5.5		
Jabra Speak 750	7700-409	2.24.0	5.5		
Jabra Link 370	14208-07 14208-08 14208-23	1.50.0			
Jabra Speak 810	7810-109 7810-209 7810-199 7810-299	1.9.0			
Jabra Speak 710	7710-309 7710-409 7710-509				
Konftel 20	931201001		5.3.4		

Device Name	Part #	Latest Tested Firmware	Latest Tested Solstice Version	Notes	
Logitech Brio	960-001105	2.6	5.5	Pair with USB speakerphone to avoid a potential remote echo. Application-based Logitech RightSense functionality not supported.	
Logitech ConferenceCam Connect	960-001013	2.1	5.1	Requires powered USB hub or power supply. Application-based Logitech RightSense functionality not supported.	
Logitech BCC950	960-000866		5.1	Application-based Logitech RightSense functionality not supported.	
Lumens VC-B11U	VC-B11U	5.2.65	5.4		
Lumens MS-10	MS-10	5.0.32			
Lumens VC-B10U	VC-B10U			Set camera to ISO mode using dip switches.	
Lyzco USB-to-3.5mm Audio Adapter		n/a			
Magewell HDMI Gen 2 Adapter	32060	n/a	5.5.2	Supported in Solstice 5.5.2. Recommended settings for best performance: 720p, 30 frames, YUY2	
Meeting Owl	Meeting Owl	3.0.2.4	5.5		
Meeting Owl Pro	Meeting Owl Pro				
Microsoft LifeCam HD-3000	T4H-00002				
Neets 4K Webcam	325-0100			Pair with USB speakerphone to avoid a potential remote echo.	
Neets Sound Bar SB1	312-0040			Requires converter.	
Neets Sound Bar SB2	312-0045				
Nureva HDL 300	HDL300-B (Black) HDL300-W (White)	2.5.72		Application-based Nureva Cloud Console management not supported.	
Nureva HDL 200	HDL200-B (Black) HDL200-W (White)	1.3.57851		Application-based Nureva Cloud Console management not supported.	
Poly EagleEye Cube	7230-61960-001	1.3.1-001267	5.5	Running a Poly device management app during a video conference may result in a frozen video feed. Mersive recommends running these apps only when not using the device.	

Device Name	Part #	Latest Tested Firmware	Latest Tested Solstice Version	Notes	
QSC PTZ 12x72	PTZ-12x72		5.5	See <a href="#">tested configuration</a> . Set to resolution of 720p in Q-SYS Designer software.	
QSC PTZ 20x60	PTZ-20x60		5.5	Set to resolution of 720p in Q-SYS Designer software.	
Sennheiser SP30T Audio Puck	1000225	1			
Sennheiser SP20 Audio Puck	506050				
Shure IntelliMix P300	MXA310AL-P300-P	4.4.13		Supports all Shure Audio Ecosystem networked microphones including MXA310, MXA710, and MXA910.	
Shure ANIUSB-Matrix	ANIUSB-MATRIX				
Stem Audio Hub	HUB1	2.2.2	5.5		
Stem Audio Table	TABLE1	2.2.2	5.5		
Ugreen USB-to-3.5mm Audio Adapter		n/a			
Vaddio AV Bridge Mini	999-8240-000	AV Bridge Mini 1.1.0 Audio - 1.05 USB - 01.02.000	5.4		
Vaddio Conference Shot 10	999-9990-000	2.4.0			
Vaddio Huddle Shot	999-50707-000	1.0.0			
Yamaha ADECIA Ceiling Solution			5.3		
Yamaha YVC-330	10-YVC330	1.2	5.3.4		
Yamaha YVC-200	10-YVC200	1.05			
Yamaha YVC-1000	10-YVC1000				